



Silver(V)



- R : Mirror
- V : Silver

Model				ARNU07GSE*2	ARNU09GSE*2	ARNU12GSE*2	ARNU15GSE*2	ARNU18GS8*2	ARNU24GS8*2
Capacity	Cooling	Nom	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	Nom	kW	2.5	3.2	4.0	5.0	6.3	8.0
Power Input	Cooling	Nom	W	40	40	40	40	35	35
	Heating	Nom	W	40	40	40	40	35	35
Power Supply			ø/V/Hz	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50	1 / 220 ~240 / 50
Airflow Rate	Cooling	H/M/L	m^3/min	7.0 / 6.0 / 4.0	8.0 / 7.0 / 5.0	10.0 / 8.0 / 6.0	10.5 / 8.0 / 6.0	14.4 / 13.0 / 11.0	17.9 / 14.4 / 12.0
	Heating	H/M/L	m^3/min	7.0 / 6.0 / 4.0	8.0 / 7.0 / 5.0	10.0 / 8.0 / 6.0	10.5 / 8.0 / 6.0	14.4 / 13.0 / 11.0	17.9 / 14.4 / 12.0
Sound Pressure		H/M/L	dBA	37 / 33 / 23	39 / 35 / 25	41 / 36 / 27	42 / 36 / 27	37 / 34 / 31	43 / 37 / 32
Dimensions	Body	WxDxH	mm	915 x 282 x 165	915 x 282 x 165	915 x 282 x 165	915 x 282 x 165	1,107 x 299 x 200	1,107 x 299 x 200
Net Weight			kg(lbs)	11.2(24.7)	11.2(24.7)	11.2(24.7)	11.2(24.7)	15(33.1)	15(33.1)
Piping Connection	Liquid		mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)
	Gas		mm(inch)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	12.7(1/2)	15.88(5/8)
	Drain	I.D.	mm(inch)	16(5/8)	16(5/8)	16(5/8)	16(5/8)	16(5/8)	16(5/8)

Note :

1. Capacities are based on the following conditions

Cooling - Indoor temp. 27°C(80.6°F)DB / 19°C(66.2°F)WB
Outdoor temp. 35°C(95°F)DB / 24°C(75.2°F)WB
Interconnecting piping length 7.5m
Level difference of zero

Heating - Indoor temp. 20°C(68°F)DB / 15°C(59°F)WB
Outdoor temp. 7°C(44.6°F)DB / 6°C(42.8°F)WB
Interconnecting piping length 7.5m
Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

Accessories

Model		ARNU07GSE*2	ARNU09GSE*2	ARNU12GSE*2	ARNU15GSE*2	ARNU18GS8*2	ARNU24GS8*2
Dry Contact	Without Case (1 Contact Point)	PQDSA					
	With Case (1 Contact Point)	PQDSB / PQDSB1					
	With Case (2 Contact Point)	PQDSBC					

Wired Remote Controller				Wireless Remote Controller
Standard Type	Standard Type	Simple Type	Simple Type for Hotel	
				
PQRCUDS0	PQRCVSL0QW	PQRCVCL0Q (Black) PQRCVCL0QW (white)	PQRCHCA0Q(Black) PQRCHCA0QW(White)	PQWRHQ0FDB